

SOLIS

— THE TOUGHEST —
PERFORMER
« FOR YOUR FIELD »

26



RELIABLE MECHANICAL
TRACTOR

POWER PACKED
ENGINE

TWIN PROJECTOR
HEADLAMPS

AGRI, IND. & TURF
TYRE OPTION

REINFORCED SAFETY
FEATURES



**COST
EFFICIENT**

MECHANICAL TRACTORS

MADE OF

**REAL
STEEL**

**STRATEGIC
COLLABORATION
WITH**

YANMAR



S26

Solis



FEATURES	S26
ENGINE	
Engine Type	MHI Engine
HP Category	26
No. of Cylinders	3
Aspiration	Natural
Cubic Capacity (cc)	1318
Rated RPM	2700
Air Cleaner	Dry Type with Clogging Sensor
Cold Start	Standard
Max Torque (Nm)	76.3 Nm
Exhaust	Downdraft Exhaust
Muffler	Under-hood
TRANSMISSION	
Drive	4WD
Clutch	Single Clutch
Gearbox	6F+2R
Front Axle	4WD
Transmission	Sliding Mesh
SPEED (FORWARD) Agri Tyre	
Maximum Speed (Km/Hr)	18.08
Minimum Speed (Km/Hr)	1.67 @ 2700 erpm Speeds May Vary with Other Tyres
BRAKES	
Brakes	Oil Immersed Brakes
Type of Actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK	
Differential Lock	Mechanical, Foot Operated
PTO	
PTO (RPM)	540/1000
PTO (Actuation)	Mechanical
STEERING	
Steering	Power
ELECTRICAL	
Battery	12V, 65Ah
Alternator	12V, 42Amp
Seven Pin Trailer Socket	Output 12V
HYDRAULICS	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Hydraulic Lifting Capacity (Kg)	600
Auxiliary Hydraulic Circuit	1DA
SAFETY SWITCH	
Clutch Safety Switch	Standard

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

FEATURES		S26		
PTO Safety Switch		Standard		
Neutral Safety Switch		Standard		
CAPACITY (Ltrs.) (+/-5%) 				
Fuel Tank (Ltr.)		26		
TURNING RADIUS 				
With Brakes (m)		2.7		
TYRE 				
Front		6.00 - 12		
Rear		8.30 - 20		
DIMENSION & WEIGHT (+/-5%) Agri Tyre 				
Weight (Kg)		995		
Wheel Base (mm)		1560		
Total Length (mm)		2760		
Total Width (mm)		1075		
Height (mm) Up to ROPS		1955		
Min. Ground Clearance (mm)		240		
Front Track (mm)		885		
Rear Track (mm)		835		
OTHERS 				
Fuel Indicator Gauge		Standard		
Front Tow Hook		Standard		
Front & Rear Weights with Std. Ballast		Front Weights - 15 x 2		
Trailer Hitch		1. Swinging Bar (Optional)		
		2. Clevis Hitch (Standard)		
		3. Semi Automatic Hitch		
Roll Over Protection		Standard		
Canopy		Optional		
OPTIONAL FEATURES 				
TYRES				
				
TURF	INDUSTRIAL	AGRI	RADIAL	GALAXY PRO
Front Tyre: 23x8.50-12	Front Tyre: 23x8.50-12	Front Tyre: 7x14	Front Tyre: 6.5/80-12	Front Tyre: 220/55 R12
Rear Tyre: 33x15.50-16.5	Rear Tyre: 33x15.50-16.5	Rear Tyre: 8.3x24	Rear Tyre: 280/70 R18	Rear Tyre: 280/70 R16
Front End Loader			Optional	

DEALER STAMP

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221

Fax:+91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com